

HP ProLiant DL320

Firewall/VPN/Cache Server

Network Information Card

Before connecting the HP ProLiant DL320 Firewall/VPN/Cache server to the network, record the following configuration information for your environment in the space provided.

Internal Network Interface IP Setup

The internal network interface (NIC 1) of the ProLiant DL320 Firewall/VPN/Cache server is the interface assigned to internal network traffic.

- Internal network interface IP address: _____
- Subnet mask: _____
- Preferred DNS server: _____
- Alternate DNS server: _____

NOTE: If you have more than two DNS servers or any WINS servers, enter their IP addresses after the ProLiant DL320 Firewall/VPN/Cache server Setup Wizard completes.

External Network Interface IP Setup

The external network interface (NIC 2) of the ProLiant DL320 Firewall/VPN/Cache server is the interface assigned to external network traffic. If you have a public static IP address (assigned by the DNS server), enter this information during setup.

External network interface IP address: _____

Subnet Mask: _____

Default Gateway: _____

Perimeter Network Interface IP Setup

The perimeter network interface (NIC 3) of the ProLiant DL320 Firewall/VPN/Cache server is optional. The interface is connected to the perimeter network (also known as DMZ). If you have a DHCP server and intend to automatically assign an IP address to NIC 3, there is no need to provide the address during setup.

Perimeter network interface IP address: _____

Computer Name

The ProLiant DL320 Firewall/VPN/Cache server must be assigned a computer name. The computer name must be 15 alphanumeric characters or less. Enter the computer name you assign below.

Computer name: _____

Administrator Password

The administrator password is the password used to log on to the ProLiant DL320 Firewall/VPN/Cache server. Define the administrator password during setup using at least six characters and a mix of uppercase and lowercase letters, numbers, and non-alphanumeric characters (for example, !, \$, #, %).

NOTE: For security reasons, HP recommends destroying any hard copy notes taken to memorize this password as soon as possible or storing the notes in a safe place.

Workgroup or Domain Name

Record the name of the Workgroup or Domain that will be joined during setup.

NOTE: A domain can be joined anytime after setup completes.

Workgroup or domain name: _____

Proceed to step 3 of the *HP ProLiant DL320 Firewall/VPN/Cache Server Quick Setup Poster*.

© Copyright 2004 Hewlett-Packard Development Company, L.P.

The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

First Edition (July 2004)
Part Number 341673-001



341673- 001